

Features

- Low forward voltage drop
- Soft recovery
- Hermetic metal cases with ceramic insulators

Typical Applications

- Inverters and choppers
- Motor control
- Snubber and free-wheeling diodes

$I_{F(AV)}$ **710A**
 V_{RRM} **1100~2000V**
 t_{rr} **3.0 μ s**



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled, T _c =85°C	150			710	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms	150	1100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			40	mA
I _{FSM}	Surge forward current	10ms half sine wave	150			9	kA
I ² t	I ² t for fusing coordination	V _R =0.6V _{RRM}					405
V _{FO}	Threshold voltage		150			1.30	V
r _F	Forward slope resistance						0.42
V _{FM}	Peak forward voltage	I _{TM} =1200A, F=7.0kN	25			2.60	V
I _{rm}	Reverse recovery current	I _{TM} =1000A, tp=1000 μ s, -di/dt=60A/ μ s, V _R =50V	150		42		A
t _{rr}	Reverse recovery time				3.0		μ s
Q _{rr}	Recovery charge				63	90	μ C
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 7.0kN				0.045	°C/W
R _{th(c-h)}	Thermal resistance case to heat sink					0.010	
F _m	Mounting force			5.3		10	kN
T _{stg}	Stored temperature			-40		160	°C
W _t	Weight				80		g
Outline	ZT25aT						

Outline:

