**Features:**

- Isolated mounting base 2500V~
- Pressure contact technology with Increased power cycling capability
- Space and weight saving

**Typical Applications**

- Various rectifiers
- DC supply for PWM inverter

$V_{RSM}$	$V_{RRM}$	Type & Outline
900V	800V	MD500-08-417F2
1100V	1000V	MD500-10-417F2
1300V	1200V	MD500-12-417F2
1500V	1400V	MD500-14-417F2
1700V	1600V	MD500-16-417F2
1900V	1800V	MD500-18-417F2

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}C)$	VALUE			UNIT
				Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Single side cooled, $T_c=100^{\circ}C$	150			500	A
$I_{F(RMS)}$	RMS forward current		150			785	A
$I_{RRM}$	Repetitive peak current	at $V_{RRM}$	150			40	mA
$I_{FSM}$	Surge forward current	10ms half sine wave $V_R=0.6V_{RRM}$	150			16.0	kA
$I^2t$	$I^2t$ for fusing coordination					1280	$A^2s \cdot 10^3$
$V_{FO}$	Threshold voltage		150			0.75	V
$r_F$	Forward slope resistance					0.30	m $\Omega$
$V_{FM}$	Peak forward voltage	$I_{FM}=1500A$	25			1.60	V
$R_{th(j-c)}$	Thermal resistance Junction to case	At 180°sine: Single side cooled per chip				0.090	$^{\circ}C / W$
$R_{th(c-h)}$	Thermal resistance case to heatsink	At 180°sine: Single side cooled per chip				0.024	$^{\circ}C / W$
$V_{iso}$	Isolation voltage	50Hz, R.M.S, $t=1min, I_{iso}=1mA(max)$		2500			V
$F_m$	Terminal connection torque(M10)				12.0		N-m
	Mounting torque(M6)				6.0		N-m
$T_{vj}$	Junction temperature			-40		150	$^{\circ}C$
$T_{stg}$	Stored temperature			-40		125	$^{\circ}C$
$W_t$	Weight				775		g
Outline	417F2						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

Outline:

